

axb-em232



The AXB-EM232 Enhanced Master/RS-232 Controller combines Access Master processing with one RS-232/422/485 and one RS-232 control port into a single compact enclosure. It is ideal for systems that need the full power of AMX Access programming but few control ports.

As an exhibit controller, the AXB-EM232 can execute pre-timed shows from two laserdisc players, or trigger presentations from switches or motion sensors (using the eight-input AXP-CPI8 Custom Panel Interface).

The AXB-EM232 can also act as a central coordinator in distributed, multi-room systems. For example, a number of rooms can be served by a Television Manager, a four-Port IR/Serial Controller and IR wireless panels, all connected to the same AXLink data/power bus.




axb-em232

AXB-EM232 INTERFACE

- Acts as AXlink Central Controller with onboard Motorola® M68340 Master processor
- Stores Access application programs in battery-backed 64K memory, upgradable to 256K
- Extends control, using AXlink CardFrames, Bus Controllers, and control panels via the AXlink data/power bus
- Controls up to two data-driven sources from internal RS-232, RS-422, and RS-485 ports
- Supports 300–38,400 baud transmission rates and data communication parameters
- Mounts into a 19.0" rack using the optional AC-RK Accessory Rack Kit, or operates as a free-standing unit

FRONT PANEL

- AXlink: Green LED indicator for AXlink data transmission
- Program: DB-9 (male) RS-232 connector to download AXCESS programs
- RS-232 Program: 8-position data transmission DIP switch for the Program connector
- TX1/RX1: Red LED indicators for data transmission on port 1
- RS-232/422 (1): 8-position communication parameter DIP switch for port 1
- RS-232/422 (2): 8-position communication parameter DIP switch for port 2
- TX2/RX2: Red LED indicators for data transmission on port 2



ENCLOSURE

- Metal with black matte finish

DIMENSIONS (HWD)

- 1.51" x 5.55" x 6.45" (3.84 cm x 14.10 cm x 16.38 cm)

WEIGHT

- 1.1 lbs (495 g)

POWER

- 12 VDC at 175 mA

REAR PANEL


- RS-232: RS-232 data communication connector (6-pin male) for port 2
- RS-232/422: RS-232/422/485 data communication connector (8-pin male) for port 1
- AXlink: AXlink bus connector (4-pin male)
- PWR: 12 VDC power supply connector (2-pin male)

INCLUDED ACCESSORIES

- AXlink connector (4-pin female)

OPTIONAL ACCESSORIES

- CC-232 RS-232 Control Cables
- AC-RK Accessory Rack Kit



IT'S YOUR WORLD. TAKE CONTROL.

ARGENTINA • AUSTRALIA • BELGIUM • BRAZIL • CANADA • CHINA • ENGLAND • FRANCE • GERMANY • GREECE • HONG KONG • INDIA • INDONESIA • ITALY • JAPAN
 LEBANON • MALAYSIA • MEXICO • NETHERLANDS • NEW ZEALAND • PHILIPPINES • PORTUGAL • RUSSIA • SINGAPORE • SPAIN • SWITZERLAND • THAILAND • TURKEY • USA
 ATLANTA • BOSTON • CHICAGO • CLEVELAND • DALLAS • DENVER • INDIANAPOLIS • LOS ANGELES • MINNEAPOLIS • PHILADELPHIA • PHOENIX • PORTLAND • SPOKANE • TAMPA
 3000 RESEARCH DRIVE, RICHARDSON, TX 75082 • 800.222.0193 • 469.624.8000 • +1.469.624.7400 • 469.624.7153 fax • www.amx.com